	Application No.	Applicant(s)	
•	10/820,257	JAIN ET AL.	
Notice of Allowability	Examiner	Art Unit	
	Dieu-Minh Le	2114	
The MAILING DATE of this communication apper All claims being allowable, PROSECUTION ON THE MERITS IS herewith (or previously mailed), a Notice of Allowance (PTOL-85) NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RI of the Office or upon petition by the applicant. See 37 CFR 1.313	(OR REMAINS) CLOSED in or other appropriate commitments. This application is	n this application. If not include unication will be mailed in due	ed course. THIS
1. \boxtimes This communication is responsive to <u>the amendment filed</u>	10/29/2007 and interview or	<u>n 12/11/2007</u> .	
2. The allowed claim(s) is/are 14-16, 18-27, 38-40, 42-48, 55-	.58, 60-66, 74-76, and 78-8	3 now as [1-43].	
3. ☐ Acknowledgment is made of a claim for foreign priority un a) ☐ All b) ☐ Some* c) ☐ None of the:		or (f).	
1. Certified copies of the priority documents have			
2. Certified copies of the priority documents have			
3. Copies of the certified copies of the priority do	cuments have been receive	d in this national stage applica	tion from the
International Bureau (PCT Rule 17.2(a)).			
* Certified copies not received:			
Applicant has THREE MONTHS FROM THE "MAILING DATE" noted below. Failure to timely comply will result in ABANDONM THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.		e a reply complying with the rec	quirements
4. A SUBSTITUTE OATH OR DECLARATION must be submit INFORMAL PATENT APPLICATION (PTO-152) which give			OTICE OF
5. CORRECTED DRAWINGS (as "replacement sheets") mus	t be submitted.		
(a) ☐ including changes required by the Notice of Draftspers	on's Patent Drawing Review	w (PTO-948) attached	
1) hereto or 2) to Paper No./Mail Date			
(b) including changes required by the attached Examiner's Paper No./Mail Date	s Amendment / Comment or	r in the Office action of	
Identifying indicia such as the application number (see 37 CFR 1, each sheet. Replacement sheet(s) should be labeled as such in the			back) of
6. DEPOSIT OF and/or INFORMATION about the deposit attached Examiner's comment regarding REQUIREMENT I			lote the
Attachment(s)	E □ Notice of In	formal Patent Application	•
 Notice of References Cited (PTO-892) Dotice of Draftperson's Patent Drawing Review (PTO-948) 		• •	
Information Disclosure Statements (PTO/SB/08),	Paper No.,	ummary (PTO-413); /Mail Date <i>/2/11 /20</i> 07. Amendment/Comment	
Paper No./Mail Date4. Examiner's Comment Regarding Requirement for Deposit	8. 🗌 Examiner's	Statement of Reasons for Allo	wance
of Biological Material	9. Other	_ •	
•		DIEU-MINH LE PRIMARY EXAMINER	

Art Unit: 2114

1. This office action is in response to the communication filed on 10/29/2007 and the Interview on 12/11/2007.

- 2. Claims 14-16, 18-27, 38-40, 42-48, 55-58, 60-66, 74-76, and 78-83 now as [1-43] are allowable over the prior art of record; claims 17, 28-37, 41, 49-54, 59, 67-73, 77, and 84-90 have been canceled.
- 3. An Examiner's Amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 C.F.R. § 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the Issue Fee.

EXAMINER'S AMENDMENT:

IN THE CLAIMS:

Please replace all prior versions of claims in the application with the current listing in the **ATTACHMENT:**

Art Unit: 2114

4. Authorization for this Examiner's Amendment was given in a telephone interview with Ms. Brenna A. Brock, Registration No. 48,509 on 12/11/2007.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dieu-Minh Le whose telephone number is (571) 272-3660. The examiner can normally be reached on Monday - Thursday from 8:30 AM to 6:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Scott Baderman can be reached on (571)272-3644. The Tech Center 2100 phone number is (571) 272-2100.

Art Unit: 2114

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

PRIMARY EXAMINER
ART UNIT 2114

DML.

11/10/2007

Art Unit: 2114

ATTACHMENT:

LISTING OF CLAIMS:

1-13. (Canceled)

14. (Previously Presented) A method comprising:

identifying a first network component in a first path using a first identifier stored in a heap data structure, wherein the first path is between a first node and a second node;

removing the first identifier from the heap data structure; identifying a second network component in a second path using a second identifier stored in the heap data structure, wherein the second identifier remains in the heap data structure subsequent to the removing the first identifier, the second path is between the first node and the second node, and the first path and the second path are disjoint;

sending a packet from the first node via the first path; and

sending a duplicate of the packet from the first node via the second path.

15. (Previously Presented) The method of claim 14, further comprising:

identifying a plurality of network components in the first path using identifiers stored in the heap data structure; and

Art Unit: 2114

removing the identifiers corresponding to the network components in the first path from the heap data structure.

16. (Previously Presented) The method of claim 15, further comprising:

storing the plurality of identifiers in the heap data structure, wherein each one of the identifiers represents a corresponding one of a plurality of network components.

17. (Canceled)

- 18. (Previously Presented) The method of claim 14, wherein the first and second network components are nodes.
- 19. (Previously Presented) The method of claim 14, wherein the first and second network components are links.
- 20. (Previously Presented) The method of claim 14, further comprising:

removing the second identifier from the heap data structure:

identifying a third network component, in a third path between the first node and the second node, using a third identifier stored in the heap data structure, wherein the third identifier remains in the heap data structure subsequent to the removing the second identifier, and the first path, the second path, and the third path are disjoint.

Application/Control Number: 10/820,257 Page 7

Art Unit: 2114

21. (Previously Presented) The method of claim 20, further comprising:

sending an additional duplicate of the packet from the first node via the third path.

22. (Previously Presented) The method of claim 14, further comprising:

associating a sequence number with each of the packet and the duplicate of the packet.

23. (Previously Presented) The method of claim 22, further comprising:

receiving both of the packet and the duplicate of the packet at the second node; and

discarding one of the packet and the duplicate in response to the sequence number associated with each of the packet and the duplicate.

- 24. (Previously Presented) The method of claim 14, wherein the identifying ones of the network elements in the first path is based on an Open Shortest Path First (OSPF) algorithm.
- 25. (Previously Presented) The method of claim 14, wherein the packet is a Voice over Internet Protocol (VoIP) packet.
- 26. (Previously Presented) The method of claim 14, wherein sending the packet comprises sending the packet according to a label-switching protocol.

Art Unit: 2114

27. (Previously Presented) The method of claim 14, further comprising:

storing cost and topology information, wherein the cost and topology information is used to identify the first path.

28-37. (Canceled)

38. (Currently Amended) A computer readable <u>storage</u> medium <u>storing comprising</u> program instructions executable <u>by a processor to:</u>

identify a first network component, in a first path between a first node and a second node, using an identifier stored in a heap data structure;

remove the identifier corresponding to the first network component from the heap data structure; [[and]]

identify a second network component, in a second path
between the first node and the second node, using a
second identifier stored in the heap data structure,
wherein the second identifier remains in the heap data
structure subsequent to removal of the first
identifier, and the first path and the second path are
disjoint;

send a packet from the first node via the first path; and send a duplicate of the packet from the first node via the second path.

39. (Currently Amended) The computer readable storage medium of claim 38, wherein the program instructions are further executable to:

Art Unit: 2114

identify a plurality of network components in the first path using identifiers stored in the heap data structure; and

remove the identifiers corresponding to the network components in the first path from the heap data structure.

40. (Currently Amended) The computer readable <u>storage</u> medium of claim 39, wherein the program instructions are further executable to:

store identifiers in the heap data structure, wherein each one of the identifiers represents a corresponding one of a plurality of network components.

41. (Canceled)

- 42. (Currently Amended) The computer readable storage medium of claim 38, wherein the first and second network components are nodes.
- 43. (Currently Amended) The computer readable <u>storage</u> medium of claim 38, wherein the first and second network components are links.
- 44. (Currently Amended) The computer readable <u>storage</u> medium of claim 38, wherein the program instructions are further executable to:

associate a sequence number with each of the packet and the duplicate of the packet.

Art Unit: 2114

- 45. (Currently Amended) The computer readable storage medium of claim 38, wherein ones of the network elements in the first path are identified based on an Open Shortest Path First (OSPF) algorithm.
- 46. (Currently Amended) The computer readable <u>storage</u> medium of claim 45, wherein the packet is a Voice over Internet Protocol (VoIP) packet.
- 47. (Currently Amended) The computer readable <u>storage</u> medium of claim 38, wherein the packet is sent according to a label-switching protocol.
- 48. (Currently Amended) The computer readable <u>storage</u> medium of claim 38, wherein the program instructions are further executable to:

store cost and topology information, wherein the cost and topology information is used to identify the first path.

49-54. (Canceled)

55. (Currently Amended) A system comprising:

means for storing a heap data structure;

- means for identifying a first network component in a first path using an identifier stored in [[a]] the heap data structure, wherein the first path is between a first node and a second node;
- means for removing the identifier corresponding to the first network component from the heap data structure;

Art Unit: 2114

- means for identifying a second network component in a second path using a second identifier stored in the heap data structure, wherein the second identifier remains in the heap data structure subsequent to removal of the first identifier, the second path is between the first node and the second node, and the first path and the second path are disjoint;
- means for sending a packet from the first node via the first path; and
- means for sending a duplicate of the packet from the first node via the second path.
- 56. (Previously Presented) The system of claim 55, further comprising:
 - means for identifying a plurality of network components in the first path using identifiers stored in the heap data structure; and
 - means for removing the identifiers corresponding to the network components in the first path from the heap data structure.
- 57. (Previously Presented) The system of claim 56, further comprising:
 - means for identifying a plurality of network components in the first path using identifiers stored in the heap data structure; and
 - means for removing the identifiers corresponding to the network components in the first path from the heap data structure.

Application/Control Number: 10/820,257 Page 12

Art Unit: 2114

58. (Previously Presented) The system of claim 55, further comprising:

means for storing identifiers in the heap data structure, wherein each one of the identifiers represents a corresponding one of a plurality of network components.

- 59. (Canceled)
- 60. (Previously Presented) The system of claim 55, wherein the first and second network components are nodes.
- 61. (Previously Presented) The system of claim 55, wherein the first and second network components are links.
- 62. (Previously Presented) The system of claim 55, further comprising:

means for associating a sequence number with each of the packet and the duplicate of the packet.

- 63. (Previously Presented) The system of claim 55, wherein ones of the network elements in the first path are identified based on an Open Shortest Path First (OSPF) algorithm.
- 64. (Previously Presented) The system of claim 55, wherein the packet is a Voice over Internet Protocol (VoIP) packet.
- 65. (Previously Presented) The system of claim 55, wherein the packet is sent according to a label-switching protocol.

Art Unit: 2114

66. (Previously Presented) The system of claim 55, further comprising:

means for storing cost and topology information, wherein the cost and topology information is used to identify the first path.

67-73. (Canceled)

- 74. (Previously Presented) A system comprising:
 - a first node;
 - a second node;
 - a first path between the first node and the second node; and
 - a second path between the first node and the second node, wherein the first node is configured to:
 - identify a first network components in the first path using a first identifier stored in a heap data structure,
 - remove the first identifier from the heap data structure,
 - identify a second network component in the second path using a second identifier stored in the heap data structure, wherein the second identifier remains in the heap data structure subsequent to removal of the first identifier, and the first path and the second path are disjoint,

send a packet via the first path, and send a duplicate of the packet via the second path.

Art Unit: 2114

75. (Previously Presented) The system of claim 74, wherein the first node is configured to:

- identify a plurality of network components in the first path using identifiers stored in the heap data structure; and
- remove the identifiers corresponding to the network components in the first path from the heap data structure.
- 76. (Previously Presented) The system of claim 75, wherein the first node is configured to:
 - store identifiers in the heap data structure, each one of the identifiers representing a corresponding one of a plurality of network components.

77. (Canceled)

- 78. (Previously Presented) The system of claim 74, wherein the first and second network components are nodes.
- 79. (Previously Presented) The system of claim 74, wherein the first and second network components are links.
- 80. (Previously Presented) The system of claim 74, wherein the first node is further configured to:
 - associate a sequence number with each of the packet and the duplicate of the packet.
- 81. (Previously Presented) The system of claim 74, wherein the first node identifies the ones of the network elements in the

Page 15

Application/Control Number: 10/820,257

Art Unit: 2114

first path based on an Open Shortest Path First (OSPF) algorithm.

- 82. (Previously Presented) The system of claim 81, wherein the packet is a Voice over Internet Protocol (VoIP) packet.
- 83. (Previously Presented) The system of claim 74, wherein the first node is sends the packet according to a label-switching protocol.

84-90. (Canceled)